

QDSP-2060

Small PC with Intel® Huron River Platform



- Intel® Huron River Platform with QM67/ HM65 chipset
- 2x DDR3 1066/1333 SO-DIMM up to 16GB
- 1x DVI-I, 1x HDMI, 1x DP, 2x GbE and 5.1 channel audio output
- SATA HDD or SSD, 1x eSATA & USB Combo Connector
- 1x CF Slot and 5x USB
- Intel® iAMT 7.0 supported
- Optional Wireless Ethernet or 3G Module

Product Overview

The QDSP-2060 is a compact size Box PC ideal for space critical applications. This embedded hardware platform features 2nd Generation Intel® Core™ i3/i5/i7 Processors, Intel® QM67 / HM65 chipset, and DDR3 1066/1333 SO-DIMM. It comes with a 2.5" SATA hard drive or SSD, Compact Flash slot, HDMI, DVI, 4x USB 2.0, USB 3.0, COM, and HD Audio.

The QDSP-2060 provides high reliability for harsh environments, compact size, high performance and is highly suited to a wide range of industrial applications such as Digital Signage, Gaming, Transportation, Surveillance, and Thin Servers.

Technical Information

Construction	
Metal Housing	
System Board	
Intel® Huron River Platform	
2nd Generation Intel® Core™ i3/i5/i7 Processors	
Intel® QM67/ HM65	
Memory	
2x DDR3 1066/1333 SO-DIMM up to 16GB	
I/O Panel	
Front I/O	
3x 3.5mm Phone Jack, support 5.1 channel audio output	
1x S/PDIF Output	
1x eSATA and USB 2.0 combo connector	
4x USB 2.0	
1x USB 3.0	
1x CF Slot	
1x Power Button (with Power LED)	
1x Storage status LED (HDD/Card reader)	
1x Wifi status LED	
1x 3G external antenna	
Rear I/O	
1x DC JACK for DC19V single power input	
1x DVI-I for DVI-D or VGA output	
1x HDMI	
1x DP	
2x RJ-45 GbE ports	
1x COM Port support RS-232/422/485 (Offer +5V/+12V selection)	
2x Wifi external antenna	

BIOS	
AMI UEFI BIOS / iAMT 7.0 supported	
Storage	
2.5" SATA HDD or SSD	
Expansion	
2 x mini PCIe slots (Optional for 3G/WiFi/Bluetooth module)	
1x SIM card slot (for 3G appliance) support user accessible	
WLAN	
IEEE 802.11 b/n/g (optional)	
Power Supply	
Input: 100-240 VAC	
Output: +19VDC, 3.95A, 75W	
Cooling	
System Fan with smart fan function	
OS Support	
Windows Xp/XPe/Windows 7 / Windows 8 / Linux	
Temperature / Humidity	
Operating: 0°C to 40°C, 0%-90%, non-condensing	
Storage: -20°C to 80°C, 0%-90%, non-condensing	
Dimensions	
200 x 35 x 153.1 mm (WxHxD)	
Weight	
1.2 Kg	
Mounting	
VESA Mount	
Certifications	
CE, FCC Class A	

QDSP-2060 I/Os

