

Full IP65 Stainless Steel Panel PC

FIP-22WB-CP

22" Stainless Steel Full-IP67 Panel PC



Specification

MB Specification:

• CPU	: Intel® Bay Trail Celeron® N2930 1.83 GHz
• Memory	: DDR3 So-DIMM 4GB (max. 8GB)
• Storage	: SATAII HDD 500GB or mSATA SSD 64GB
• Graphic	: Integrated Intel® HD Graphics
• Ethernet	: Intel® Intel WG82574L GbE
• BIOS	: AMI 16 MB Flash
• WiFi	: 802.11 b/g/n (Optional)
• I/O Chipsets	: Fintek F81866

System Specification:

• Housing Material	: Stainless Steel with deactivated coating for anti-corrosion
• Dimensions	: 541 x 337 x 55.8 (WxHxD) (mm)
• Keypad	: 1x On/Off button, 1x Reset button
• Mounting Type	: VESA mount

IP65 Input / Output :

• COM	: 1 x COM
• LAN	: 1 x GbE LAN port
• USB	: 2 x USB 2.0
• WLAN	: 1 x WLAN Antenna (optional)
• Power Input	: 1 x AC input

Features:

- Full-HD 1080p Input
- Anti-Corrosion Stainless Design
- Deactivated Surface Coating
- Full-IP67 Protection
- Intel Baytrail platform

Panel Specification :

• Size/ Type	: 21.5" TFT LCD
• Resolution	: 1920 x 1080
• Brightness	: 300 (cd/m <sup>2</sup> )
• Contract Ratio	: 1000 : 1 (typ.)
• Viewing Angle	: -85~85 (H) ; -80~80 (V)
• Max. Colors	: 16.7 M (8bits/color)
• Touch	: P-cap multi-touch screen

Power Specification:

• Power Input	: 90~260V AC Input (IP66 Connector)
• Consumption	: 40 W typical, normal operation
• Management	: VESA DPMS compliant
• Power Cord	: 1x 1.8m AC Power Code (EU type)
• Power Adapter	: No Power Adapter

Environment Tolerance:

• Operating Temperature	: 0 deg. C to 50 deg. C
• Storage Temperature	: -20 deg. C to 70 deg. C
• Operating Humidity	: 10% to 95% (Non Condensing)
• IP Grade	: Full- IP67

Drawings

