

Full IP65 Panel PC

FIP-15RJ

15" Stainless Full IP65 (Intel Baytrail Platform)



Features:

- Ultra Low Power Intel Baytrail Platform
- 5-wire Resistive Touch Screen (Default)
- -5~55°C Wide Range Operating Temperature
- Anti-Corrosion Stainless Bezel
- Full-IP65 Protection
- High Brightness: 1000 nits for optional

Specification

System:

- CPU : Intel Baytrail J1900, up to 2.58Ghz
- Chipset : Intel SoC integrated
- Memory : DDR3 1066MHz SO-DIMM, Default 4GB
- Storage : mSATA SSD, default 64GB
- Ethernet : Realtek RTL8111G GbE Controller
- BIOS : AMI EFI 64Mbit SPI

Input / Output :

- Serial Ports : 1 x RS232 (IP65)
- USB Ports : 2 x USB (IP65)
- Ethernet : 1 x RJ45 GbE LAN (IP65)
- Power : AC 110~240V, Universal, $\pm 10\%$ (IP65)

Power Specification :

- Power Adapter : N/A
- Power Consumption : 40W (typ.)

Panel Specification :

- Size/ Type : 15" TFT LCD
- Resolution : 1024 x 768
- Brightness : 250 (cd/m²)
- Contract Ratio : 500 : 1 (typ.)
- Viewing Angle : -70~70 (H) ; -60~60 (V)
- Max. Colors : 16.2M (6bits+ FRC)
- Touch : 5-wire resistive touch (default)

Environment Tolerance:

- Operating Temperature : -5 deg. C to 55 deg. C
- Operating Humidity : 10% to 95% (Non Condensing)
- IP65 : Full- IP65

Order Options :

- OS : Windows 7 Professional(Optional)
- High Brightness : 1000 cd/m² (Optional)
- Touch Screen : 5-wire resistive touch screen or P-cap multi-touch (Optional)
- Power Input : 9~36V DC Input (Optional)

Drawings:

