

Slim Type Full IP66 Panel PC

FIP-19RBS

19" Stainless Full-IP66 (Intel Baytrail Platform)



Features:

- Ultra Low Power Intel Celeron Quad Core N2930 1.83Ghz
- Either AR glass or Touch Screen in front
- Anti-Corrosion Stainless Housing Design
- Full-IP66 Protection
- High Brightness: 1000 nits for optional
- Flat surface and round edge

Specification

System:

- CPU : Intel Celeron M N2930 1.83Ghz
- Chipset : Intel NM10 Chipset
- Memory : DDR3 1066MHz SO-DIMM, Default 4GB
- Storage : 1x 2.5"HDD 500GB or SSD 64GB either one
- Ethernet : Broadcom BCM57780 GbE Controller
- BIOS : AMI 16Mbit Flash
- Power : AC Input
- WiFi : 802.11 b/g/n (Optional)

Input / Output :

- Serial Ports : 2 x RS232 (IP66 connectors)
- USB Ports : 2 x USB 2.0 (IP66 connectors)
- Ethernet : 1 x RJ45 GbE LAN (IP66 connectors)
- Power : AC Input (IP66)
- Buttons : 1 x Power On/Off, 1 x Reset Button

Power Specification :

- Power Adapter : No power adapter
- Power Consumption : 50W (typ.)

Panel Specification :

- Size/ Type : 19" TFT LCD
- Resolution : 1280 x 1024
- Brightness : 350 (cd/m²)
- Contract Ratio : 1000 : 1 (typ.)
- Viewing Angle : -85~85 (H) ; -80~80 (V)
- Max. Colors : 16.7 M (6bits)
- Touch : Either 5-wire resistive or P-cap touch

Environment Tolerance:

- Operating Temperature : -10 deg. C to 55 deg. C
- Operating Humidity : 10% to 95% (Non Condensing)
- IP level : Full- IP66

Order Options :

- OS : Windows 7 Professional(Optional)
- Enhance Visibility : 1,000 nits Sunlight Readable Display (Optional)
- Touch Screen : P-cap touch screen (Optional)
- Power Input : Wide range DC Input (Optional)
- IP67 : Full-IP67 (Optional)

Drawings:

