

15.0" Full-IP65 Touch Monitor



Specification

System Spec.:

• VGA	: 1 x VGA (IP65 connector)
• DVI	: 1 x DVI (IP65 connector) (optional)
• HDMI	: NA
• Video	: S-Video, Composite (optional)
• USB	: 1 x USB for touch (IP65 connector)
• Power Input	: 1 x 12V DC input (IP65 connector)
• Housing	: Stainless steel with deactivated coating
• Mounting	: 100x100 VESA Mount

Environment Tolerance:

• Operating Temperature	: -5 deg. C to 50 deg. C
• Storage Temperature	: -30 deg. C to 70 deg. C
• Humidity	: 10 to 95% (Non Condensing)
• MTBF	: 50,000 hours
• IP Grade	: Full-IP65

Power Specification :

• Power Input	: 1 x AC 100~240V, Universal \pm 10%
• Power Consumption	: 30 watts (typical)

Panel Specification :

• Size/ Type	: 15" (4:3) LED Backlight LCD
• Resolution	: 1024 x 768 @60Hz, 75Hz
• Brightness	: 250 (cd/m ²)
• Contract Ratio	: 500 : 1 (typ.)
• Viewing Angle	: -70~70 (H) ; -60~60(V)
• Max. Colors	: 16.2M (6 bits + FRC)
• Touch	: 5- wire resistive touch screen or P-cap Touch Screen (Optional)

OSD :

• OSD Input	: 5-key OSD buttons
• OSD Function	: Contrast, Color, Position, Auto-adjustment, Factory Settings

Drawings

