

Slim Type Full IP66 Monitor

FIP-19R

19" Stainless Full IP66 Rugged Touch Monitor



5-wire resistive touch /Glass



P-cap touch

Features:

- Either 5-Wire Resistive Or P-Cap Touch Screen
- -15~60°C Wide Range Operating Temperature
- Anti-Corrosion Stainless Housing Design
- Full-IP66 Protection
- High Brightness: 1000 nits for optional
- Slim, Arch edge Design

Specification

System:

• Housing Material	: Stainless Steel SUS304
• Surface Coating	: Anti-corrosion Passivated surface
• Plug & Play	: VEA DDC 1/2B
• Power Management	: VESA DPMS Compliance

Input / Output :

• VGA	: 1 x VGA (IP66 connector)
• DVI	: 1 x DVI (Optional, IP66 connector)
• Video	: 1 x Video (Optional, IP66 connector)
• HDMI	: 1 x HDMI (Optional, IP66 connector)
• USB	: 1 x USB for touch screen (IP66 connector)

Power Specification :

• Power Input	: 1 x 12V DC Input (w/external AC/DC adapter)
• Power Consumption	: 35 W (typ.)

OSD :

• OSD Input	: 5-key OSD IP66 membrane board
• OSD Function	: Contrast, Color, Position, Auto-adjustment, Factory Settings

Panel Specification :

• Size/ Type	: 19" TFT LCD
• Resolution	: 1280 x 1024
• Brightness	: 350 (cd/m²)
• Contract Ratio	: 1000 : 1 (typ.)
• Viewing Angle	: -85~85 (H) ; -80~80 (V)
• Max. Colors	: 16.7 M (6bits)
• Touch	: 5- wire resistive touch screen (default)

Environment Tolerance:

• Operating Temperature	: -15 deg. C to 60 deg. C
• Operating Humidity	: 10% to 95% (Non Condensing)
• IP66	: Full- IP66 / IP69K

Accessory :

• Power adapter	: 1 x 1.5m power adapter with power cord
• Signal cable	: 1 x 1.5m VGA cable (default) 1 x 1.5m DVI cable (optional) 1 x 1.5m Video (BNC) cable (optional)
• Driver CD	: 1 x Touch driver CD (Optional)

Drawings:

