

FIP-32W

- LED Backlight Display
- Full-HD 1080p Input
- Anti-Corrosion Stainless Design
- Deactivated Surface Coating
- Full-IP65 Protection

IP65 Input / Output :

• VGA	: 1 x VGA (IP65 connectors)
• DVI	: 1 x DVI-D (IP65 connectors)
• HDMI	: NA
• Video	: NA
• USB	: 1 x USB for touch (optional)
• Power Input	: 1 x AC input

• Housing Material	: Stainless Steel with deactivated coating for anti-corrosion
• Dimensions	: 785 x 475 x 77.4 (WxHxD) (mm)
• Weight	: 32KG
• OSD Control	: Auto video input detected
• Speakers	: 2 x 2W speakers integrated (Optional)
• Protective Glass	: 1 x 3mm thickness protective glass
• Mounting Type	: VESA mount

• Power Input	: 90~260V AC Input (IP65 Connector)
• Consumption	: 40 W typical, normal operation
• Management	: VESA DPMS compliant
• Power Cord	: 1x 1.8m AC Power Code (EU type)
• Power Adapter	: No Power Adapter

• Size/ Type	: 32" LCD (LED backlight)
• Active Area (mm)	: 698.4 (H) x 392.85 (V)
• Pixel Pitch (mm)	: 0.3638 (H)x 0.3638 (V)
• Resolution	: 1920 x 1080 @ 60Hz
• Contrast Ratio	: 3000 : 1 (typ.)
• Max. Colors	: 16.7M colors
• Brightness	: 450 nits (cd/m ²)
• Viewing Angle	: -89 ~ 89 (H); -89 ~ 89 (V)
• Glass	: AR protective glass

• Operating Temperature	: 0 deg. C to 50 deg. C
• Storage Temperature	: -20 deg. C to 70 deg. C
• Operating Humidity	: 10% to 95% (Non Condensing)
• IP65	: Full- IP65

- Touch Screen : IR touch screen (optional)
- High Brightness : 1,000 nits high brightness

Technical drawing of a rectangular structure, likely a table or bench, showing dimensions in millimeters (mm). The drawing includes a top view and a side view.

Top View Dimensions:

- Overall width: 785.0
- Inner width: 570.0
- Left side width: 42.0
- Right side width: 42.0
- Inner length (left): 350.5
- Inner length (right): 350.5

Side View Dimensions:

- Overall height: 77.4
- Inner height: 40.0
- Bottom section height: 197.5
- Top section height: 197.5

