

# Industrial LCD Touch Display

## LPM-10R

### 10.4" Panel Mount Touch Monitor



#### Specification

Input Interface :	
• VGA	: 1 x VGA D-Sub 15 pin
• DVI	: 1 x DVI-D
• HDMI	: 1 x HDMI (for optional)
• Video	: S-Video, Composite (optional)
• USB	: 1 x USB for touch
• Power Input	: 1 x 12V DC input

Power Specification:	
• Power Adapter	: 12V output adapter
• Consumption	: 18W typical, normal operation
• Management	: VESA DPMS compliant
• Power Cord	: Provided by region

Environment Tolerance:	
• Operating Temperature	: 0 deg. C to 55 deg. C
• Storage Temperature	: -20 deg. C to 70 deg. C

Panel Specification :	
• Size/ Type	: 10.4" LCD
• Active Area (mm)	: 211.2 (H) x 158.4 (V)
• Pixel Pitch (mm)	: 0.264(H) x 0.264(V)
• Resolution	: 1024 x 768 @ 60Hz, 75Hz
• Contrast Ratio	: 1200 : 1 (typ.)
• Max. Colors	: 16.2M (8 bits / color)
• Brightness	: 500 nits (cd/m <sup>2</sup> )
• Viewing Angle	: -88 ~ 88 (H); -88 ~ 88(V)
• Touch	: 5-wire resistive touch or P-cap touch screen (USB)

OSD :	
• OSD Input	: 5-key OSD buttons
• OSD Function	: Contrast, Color, Position, Auto-adjustment, Factory Settings

Order Information :	
• Power Input	: 9~36V DC Input (optional)
• Glass	: AR glass protection (optional)
• Speaker	: 1W Speaker x2 (optional)
• High Brightness	: 1000 nits (optional)

#### Drawings

