

EBOX-33xxMX Series, LAN x 1

Model Type	3300MX	3300MX-M	3300MX-H	3300MX-C	3300MX-C22	3300MX-C85
	3310MX	3310MX-M	3310MX-H	3310MX-C	3310MX-C22	3310MX-C85
Processor	DM&P Vortex86MX for 3300MX Series/ Vortex86MX + for 3310MX Series (933MHz)					
BIOS	AMI BIOS					
Memory	Onboard 512MB DDR2 for 3300MX Series/ Onboard 1GB DDR2 for 3310MX Series					
VGA	Integrated Graphics Chip/ D-Sub 15-pin					
Maximum Resolution	1600 x 1200 pixels for 3300MX Series/ 1920 x 1200 pixels for 3310MX Series					
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)					
USB 2.0	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port					
HD Audio	Mic in and Line out					
I/O	SD Slot	1x				
	SATA	1x	N/A	1x	N/A	N/A
	PS2	PS/2 for Keyboard/ Mouse x 1				
	RS-232	3x	N/A	N/A	3x	2x
	RS-422	N/A	N/A	N/A	N/A	1x
	RS-485	N/A	N/A	N/A	N/A	1x
Power	DC +8V~+15V					
Dimensions	115 x 115 x 35mm					
Unit Net Weight	500g					
Operation Temp.	5~50°C					
Certifications	CE, FCC, VCCI					
Note	COM1 (Full 9pin RS-232), COM2 with Y cable extended to COM3 & COM4 (Support TX & RX signals only)					

Features:

- DM&P Vortex86MX/ Vortex86MX+ (933MHz)
- Onboard 512MB/ 1GB DDR2
- SATA DOM, 2.5" HDD, SSD support (Optional)
- mSATA support (mSATA to SATA adapter required)
- SD, SDHC support
- TV-Out support (Optional)
- VESA mounting support
- Fanless design
- 10/100 Mbps LAN x 1
- WiFi Dongle support (Optional)
- PXE Diskless Boot
- USB 2.0 port x 4
- RS-232 Up to 3 ports (Optional)
- RS-485 x 1 port (Optional)
- RS-422 x 1 port (Optional)
- Auto Power On support
- Ultra low power