

Full IP65 Stainless Steel Panel PC

FIP-22WJ

22" Stainless Steel Full-IP65 Panel PC



Features:

- Full-HD 1080p Input
- Anti-Corrosion Stainless Design
- Deactivated Surface Coating
- Full-IP67 Protection
- Intel Baytrail platform

Specification

MB Specification:

• Processor	: Intel® Baytrail-M Celeron J1900 2.0 Ghz
• Chipset	: Intel® SoC integrated
• Memory	: DDR3 1333 SO-DIMM 4GB (default)
• Storage	: Default mSATA SSD 64GB or 2.5" HDD500GB
• Ethernet	: Dual Realtek RTL8111G GbE Controller
• Audio	: Realtek ALC269
• mPCIe	: 1(half size) + 1(full size) shared with mSATA
• WLAN	: 802.11 b/g/n 2x2 Dual Band (Optional)

System Specification:

• Housing Material	: Stainless Steel with deactivated coating for anti-corrosion
• Dimensions	: 541 x 337 x 55.8 (WxHxD) (mm)
• Keypad	: 1x On/Off button, 1x Reset button
• Mounting Type	: VESA mount

IP65 Input / Output :

• COM	: 1 x RS232
• LAN	: 1 x GbE LAN port
• USB	: 2 x USB 2.0
• WLAN	: 1 x WLAN Antenna (optional)
• Power Input	: 1 x AC input

Panel Specification :

• Size/ Type	: 21.5" TFT LCD
• Resolution	: 1920 x 1080
• Brightness	: 300 (cd/m ²) (1,000 nits high brightness for optional)
• Contract Ratio	: 1000 : 1 (typ.)
• Viewing Angle	: -85~85 (H) ; -80~80 (V)
• Max. Colors	: 16.7 M (8bits/color)
• Touch	: P-cap multi-touch screen (optional)

Power Specification:

• Power Input	: 90~260V AC Input (IP65 Connector)
• Consumption	: 60 W typical, normal operation
• Management	: VESA DPMS compliant
• Power Cord	: 1x 1.8m AC Power Code
• Power Adapter	: No Power Adapter

Environment Tolerance:

• Operating Temperature	: 0 deg. C to 50 deg. C
• Storage Temperature	: -20 deg. C to 70 deg. C
• Operating Humidity	: 10% to 95% (Non Condensing)
• IP Grade	: Full- IP65

Drawings

