

Full IP65 Industrial Monitors

FIP-55W

55" Stainless steel Full-IP65 Display



- Features:**
- Full-HD 1080p
 - 0~50°C Operating Temperature
 - Anti-Corrosion coating
 - Full-IP65 Protection for outdoor application



2 x 6ft IP65 DVI cables



1 x 6ft IP65 VGA cable



1 x 6ft IP65 AC power cables

Specification

IP65 Input / Output :

- DVI Input : 1 x DVI (IP65 Connector)
- VGA Input : 1 x VGA (IP65 Connector)
- Power Input : AC 110~240V, Universal, $\pm 10\%$ (IP65)
- HDMI Input : 1 x HDMI (Optional) (IP65 connectors)

System Specification:

- Housing Material : Stainless Steel with deactivated surface coating for anti-corrosion
- Dimensions : 131.3 x 78.4 x 10.0 (cm)
- OSD Control : Auto-detective video input
- Light Sensor : N/A (Optional)
- High Brightness : 900 nits high brightness (Optional)
- Protective Glass : AR anti-shattered protective glass
- Mounting Type : Wall mount / Hanging

Power Specification :

- Power Adapter : N/A
- Power Consumption : 110 W (typ.)
- Power Cord : Provided by region

Panel Specification :

- Size/ Type : 55" LCD
- Resolution : 1920 x 1080, Full-HD Supported
- Brightness : 450 (cd/m²)
- Contract Ratio : 5000 : 1 (typ.)
- Viewing Angle : -89~89 (H) ; -89~89 (V)
- Max. Colors : 1073.7 M (8bits/color)
- Pixel Pitch : 0.63 (H) x 0.63 (W)
- Display Area : 1209.6(H) x 680.4(V)

Environment Tolerance:

- Operating Temperature : 0 deg. C to 50 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C
- Operating Humidity : 10% to 95% (Non Condensing)
- IP65 : Full- IP65

Order Options :

- Speakers : 5W x 2 Speakers
- High Brightness : 900 nits sunlight readable
- VESA Mount Kits : 1 x VESA or Pipe Mount kit

Drawing

