




# IntesisBox® PA-AW2-MBS-1

## Modbus Interface for PANASONIC Air-to-Water Systems Aquarea H Generation



The PA-AW2-MBS-1 interface allows a complete and natural integration of **Panasonic Air-to-Water Systems** into Modbus RTU (EIA-485) networks. Compatible with Aquarea H Generation models from Panasonic.

- Reduced dimensions. 93 x 53 x 58 mm. / 3.7" x 2.1" x 2.3"
- Quick and easy installation. *Mountable on DIN rail, wall, or even inside the Hydro Unit.*
- External power not required.
- Direct connection to Modbus RTU (EIA-485) networks. Up to 63 PA-AW2-MBS-1 devices can be connected in the same network. PA-AW2-MBS-1 is a Modbus Slave device.
- Direct connection to the Hydro unit. Up to 1 Hydro unit can be connected to PA-AW2-MBS-1. *The cable for this connection is also supplied.*
- Configuration from both on-board DIP-switches and Modbus RTU.
- Total Control and Supervision.
- Real states of the Hydro unit's internal variables.
- Allows using simultaneously use of remote controls of the Hydro Unit and Modbus RTU.

## 1. **Modbus Interface**

### 1.1 **Modbus Functions**

PA-AW2-MBS-1 implements the following standard Modbus functions:

- *3: Read Holding Registers*
- *4: Read Input Registers*
- *6: Write Single Register*
- *16: Write Multiple Registers* (Despite this function is allowed, the interface does not allow write operations on more than 1 register with the same request, this means that *length* field should always be 1 when this function is being used to write).

### 1.2 **Modbus Communication parameters**

PA-AW2-MBS-1 implements a Modbus RTU (Slave) interface, to be connected to an EIA-485 line. The communication parameters are:

8N2 communication (8 data bits, no parity and 2 stop bit). It also supports 8N1 communication (1 stop bit). No need to change settings of DIP-switches.

Configurable baud rates:

- 2400 bps
- 4800 bps
- 9600 bps (Default value)
- 19200 bps
- 38400 bps
- 57600 bps
- 76800 bps
- 115200 bps

## 2. **List of compatible Panasonic Hydro indoor units.**

A list of Panasonic indoor unit model references compatible with PA-AW2-MBS-1 and their available features can be found at:

[https://www.intesisbox.com/intesis/support/compatibilities/IntesisBox\\_PA-AW2-xxx-1\\_Compatibility.pdf](https://www.intesisbox.com/intesis/support/compatibilities/IntesisBox_PA-AW2-xxx-1_Compatibility.pdf)

### 3. Electrical and Mechanical features

Enclosure	Plastic, type PC (UL 94 V-0) Net dimensions (dxwxh): 93 x 53 x 58 mm / 3.7" x 2.1" x 2.3" Color: Light Grey. RAL 7035	Operation Temperature	0°C to +60°C
Weight	85 g.	Stock Temperature	-20°C to +85°C
Mounting	Wall DIN rail EN60715 TH35.	Operational Humidity	<95% RH, non-condensing
Terminal Wiring (for low-voltage signals)	For terminal: solid wires or stranded wires (twisted or with ferrule) 1 core: 0.5mm <sup>2</sup> ... 2.5mm <sup>2</sup> 2 cores: 0.5mm <sup>2</sup> ... 1.5mm <sup>2</sup> 3 cores: not permitted	Stock Humidity	<95% RH, non-condensing
Modbus RTU port	1 x Serial EIA485 Plug-in screw terminal block (2 poles): A, B Compatible with Modbus RTU EIA-485 networks	Isolation voltage	1500 VDC
Hydro unit port	1 x Specific connector Specific cable included	Isolation resistance	1000 MΩ
Switch 1 (SW1)	1 x DIP-Switch for Hydro Unit features	Protection	IP20 (IEC60529)
Switch 3 (SW3)	1 x DIP-Switch for Modbus RTU settings	LED indicators	2 x Onboard LED - Operational status
Switch 4 (SW4)	1 x DIP-Switch for extra functions		

### 4. Connections

PA-AW2-MBS-1 connects directly to the Hydro unit. Use the EIA485 connector in the PA-AW2-MBS-1 to connect to the Modbus network.

