

FIP-15RBS

15" Stainless Full IP66 / IP69K (Intel Baytrail Celeron-M Platform)



Features:

- Ultra Low Power Celeron N2930 1.83GHz Quad Core Processor
- Either 5-Wire Resistive Or P-Cap Touch Screen
- -10~55°C Operating Temperature
- Anti-Corrosion Stainless Housing Design
- Full-IP66/ IP69K Protection
- High Brightness: 1000 nits for optional
- Elegant, Slim, Round edge design

Specification

System:

• CPU	: Intel Celeron M N2930 1.83Ghz
• Chipset	: Intel NM10 Chipset
• Memory	: DDR3 1066MHz SO-DIMM, Default 4GB
• Storage	: 1 x SSD mSATA 64GB or 128GB
• Ethernet	: Broadcom BCM57780 GbE Controller
• BIOS	: AMI 16Mbit Flash
• Power	: 100~220V AC Input
• Antenna	: Built-in 2.5G/5G internal antennas (Optional)

Input / Output (default):

- Serial Ports : 2 x RS232 (IP66)
- USB Ports : 2 x USB (IP66)
- Ethernet : 1 x RJ45 GbE LAN (IP66)
- Power : 1x AC Input (IP66)

Power Specification :

- Power Adapter : No power adapter (for optional)
- Power Consumption : 30W (typ.)

Panel Specification :

• Size/ Type	: 15" TFT LCD
• Resolution	: 1024 x 768
• Brightness	: 250 (cd/m ²)
• Contract Ratio	: 500 : 1 (typ.)
• Viewing Angle	: -70~70 (H) ; -60~60 (V)
• Max. Colors	: 16.2M (6bits+ FRC)
• Touch	: True flat 5-wire resistive touch (default)

Environment Tolerance:

- Operating Temperature : -10 deg. C to 55 deg. C
- Operating Humidity : 10% to 95% (Non Condensing)
- IP level : Full- IP66 / IP69K

Order Options :

• OS	: Windows 7 Professional(Optional)
• High Brightness	: 1000 cd/m ² (Optional)
• Touch Screen	: 5-wire resistive touch (Optional)
• Power Input	: AC Input (Optional)
• Custom I/O port	: By request
• Platform	: Intel® Haswell Core i5 4200U (Optional)

Drawings:

