

Full IP65 Monitor
FIP-27W

27" Stainless steel Full-IP65 monitor



Features:

- 5-wire Resistive Touch Screen (Default)
- -10~55°C Wide Range Operating Temperature
- Anti-Corrosion Stainless Bezel
- Full-IP65 Protection
- High Brightness: 1000 nits for optional

Specification

System:

- Front Glass : Either P-cap touch or AR glass in front
- Housing : Stainless steel in whole enclosure
- Connector : IP65 Connectors at back side
- Mounting : VESA 100, 200 at back side
- OSD : 5-key OSD control buttons
- Plug&Play : VESA DDC 1/2B

Input / Output :

- VGA : 1 x VGA Input (IP65 connector)
- USB Ports : 1 x USB for touch option (IP65 connector)
- DVI : 1 x DVI In (IP65 connector) (optional)
- Power : DC 12V (IP65 connector)

Power Specification :

- Power Adapter : 1 x AC/DC power adapter
- Power Consumption : 35W (typ.)
- Power Cord : 1 x 1.8m AC power cord

Panel Specification :

- Size/ Type : 27" LCD (LED backlight)
- Active Area (mm) : 597.6 (H) x 336.15 (V)
- Pixel Pitch (mm) : 0.31125 (H)x 0.31125 (V)
- Resolution : 1920 x 1080 @ 60Hz
- Contrast Ratio : 3000 : 1 (typ.)
- Max. Colors : 16.7M colors
- Brightness : 300 nits (cd/m²)
- Viewing Angle : -89 ~ 89 (H); -89 ~ 89 (V)

Environment Tolerance:

- Operating Temperature : 0 deg. C to 55 deg. C
- Operating Humidity : 10% to 95% (Non Condensing)
- IP65 : Full- IP65

Order Options :

- High Brightness : 1000 cd/m² (Optional)
- Power Input : AC Input (Optional)
- Custom I/O : By request

Drawings:

