

Full IP65 Stainless Steel Monitor

FIP-42W

42" Stainless Steel Full-IP65 Display



Features:

- LED Backlight Display
- Full-HD 1080p Input
- Anti-Corrosion Stainless Design
- Deactivated Surface Coating
- Full-IP65 Protection

Specification

IP65 Input / Output :

• VGA	: 1 x VGA (IP65 connectors)
• DVI	: 1 x DVI-D (IP65 connectors)
• HDMI	: NA
• Video	: NA
• USB	: 1 x USB for touch (optional)
• Power Input	: 1 x AC input

System Specification:

• Housing Material	: Stainless Steel with deactivated coating for anti-corrosion
• Dimensions	: 104.1 x 63.3 x 8 (WxHxD) (cm)
• Weight	: 38KG
• OSD Control	: Auto video input detected
• Speakers	: 2 x 2W speakers integrated (Optional)
• Protective Glass	: 1 x 3mm thickness protective glass
• Mounting Type	: VESA mount and 3x hangers

Power Specification:

• Power Input	: 90~260V AC Input (IP65 Connector)
• Consumption	: 95 W typical, normal operation
• Management	: VESA DPMS compliant
• Power Cord	: 1x 1.8m AC Power Code (EU type)
• Power Adapter	: No Power Adapter

Panel Specification :

• Size/ Type	: 42" LCD (LED Backlight)
• Resolution	: 1920 x 1080
• Brightness	: 350 (cd/m²)
• Contract Ratio	: 1500 : 1 (typ.)
• Viewing Angle	: -89~89 (H) ; -89~89 (V)
• Max. Colors	: 16.7 M (8bits/color)
• Glass	: AR glass (Default)

Environment Tolerance:

• Operating Temperature	: 0 deg. C to 50 deg. C
• Storage Temperature	: -20 deg. C to 70 deg. C
• Operating Humidity	: 10% to 95% (Non Condensing)
• IP65	: Full- IP65

Order Options :

• Touch Screen	: IR touch screen (optional)
• High Brightness	: 1,000 nits high brightness

Drawings

