

LCD Touch Display

LCH-24W

24" LCD Monitor



Specification

Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-D
- HDMI : 1 x HDMI (optional)
- Video : 1 x AV (optional)
- USB : 1 x USB for touch (optional)
- Power Input : 1 x AC input

Power Specification:

- Power Adapter : N/A
- Consumption : 60 W typical, normal operation
- Input : AC Input
- Power Cord : N/A

Environment Tolerance:

- Operating Temperature : 0 deg. C to 50 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C
- IP Grade : Front IP65, Rear IP54

Touch Screen:

- Touch Screen : 5-wire resistive touch (optional)
P-Cap touch (optional)

Panel Specification :

- Size/ Type : 24" LCD (LED backlight)
- Active Area (mm) : 531.36 (H) x 289.89 (V)
- Pixel Pitch (mm) : 0.27675 (H)x 0.27675 (V)
- Resolution : 1920 x 1080 @ 60Hz
- Contrast Ratio : 5000 : 1 (typ.)
- Max. Colors : 16.7M colors
- Brightness : 350 nits (cd/m²)
- Viewing Angle : -89 ~ 89 (H); -89 ~ 89 (V)

OSD :

- OSD Input : 5 -key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

Order Information :

- Touch : P-cap multi-touch (optional)
- Speaker : 2W Speaker x2 (optional)
- High Brightness : 1000 nits (optional)

Drawings

