

# Full Flat Type

# LFS-10R

## 10.4" LCD (LED backlight) Projective Capacitive Touch Monitor



### Features:

- \* Heavy Duty Metal Steel
- \* Aluminum Front Bezel
- \* 9~36V Wide Range DC power Input

### Specification

#### Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-I input (optional)
- HDMI : 1 x HDMI input
- Video : S-Video, Composite (optional)
- USB : 1 x USB for touch screen
- Power Input : 1 x 12V DC input

#### Power Specification:

- Power Adapter : 1 x AC to DC Power adapter
- Consumption : 15 W typical, normal operation
- Management : VESA DPMS compliant
- Power Cord : Provided by region

#### Environment Tolerance:

- Operating Temperature : -5 deg. C to 50 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C
- Water/Dust proof : Front IP65
- Vibration : 5Hz~500Hz / 1Grms/3 Axis
- Shock : MIL-STD-810G Method 516.6 Procedure I, Up to 50G/11ms

#### Panel Specification :

- Size/ Type : 10.4" TFT LCD
- Resolution : 1024 x 768
- Brightness : 1,000 (cd/m<sup>2</sup>) Sunlight Readable
- Contrast Ratio : 500 : 1 (typ.)
- Viewing Angle : -88~88 (H) ; -88~88 (V)
- Max. Colors : 16.2M
- Touch : P-cap multi touch screen (USB)

#### OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings

#### Order Information :

- Optical Bonding : Optical Bonding (for optional)
- Speaker : 2W Speaker x2 (optional)
- High Brightness : 1000 nits (optional)

### Drawings

