

LFS-15W

15.6" (16:9) Wide LCD Touch Monitor



Features:

- LED Backlight Display
- -5~55°C Wide Range Operating Temperature
- Projected Capacitive Multi Touch Screen
- Front-IP65 Protection

Specification

Input / Output :	
• VGA	: 1 x VGA D-Sub 15 pin
• DVI	: 1 x DVI-I input (optional)
• HDMI	: 1 x HDMI input (optional)
• Video	: S-Video, Composite (optional)
• USB	: 1 x USB for touch screen
• Power Input	: 1 x DC input w/external power adapter

Power Specification:	
• Power Adapter	: 1 x AC/DC Power Adapter
• Consumption	: 16 W typical, normal operation
• Management	: VESA DPMS compliant
• Power Cord	: Provided by region

Environment Tolerance:	
• Operating Temperature	: -15 deg. C to 60 deg. C
• Storage Temperature	: -20 deg. C to 70 deg. C
• Operating Humidity	: 10% to 95% (Non Condensing)
• IP65	: Front IP65
• Vibration	: 5 Hz ~ 500 Hz/ 1 Grms/ 3 Axis
• Shock	: 15G, 11ms duration

Panel Specification :	
• Size/ Type	: 15.6" (16:9) LED backlight
• Active Area (mm)	: 344 (H) x 194 (V)
• Pixel Pitch (mm)	: 0.3 (H)x 0.3 (V)
• Resolution	: 1920 x 1080 @ 60Hz
• Contrast Ratio	: 500 : 1 (typ.)
• Max. Colors	: 262K colors(6 bits )
• Brightness	: 400 nits (cd/m²)
• Viewing Angle	: -80 ~ 80 (H); -70 ~ 70 (V)
• Touch Screen	: P-cap multi touch screen

OSD :	
• OSD Input	: 5-key OSD buttons
• OSD Function	: Contrast, Color, Position, Auto-adjustment, Factory Settings

Order Options :	
• Touch Screen (Optional)	: 5-Wire resistive touch screen
• High Brightness (Optional)	: 1,000 nits high brightness
• VESA Mount Kit (Optional)	: 1 x VESA or Pipe Mount kit

Drawings

