

# Stainless Steel LCD Monitor

## LST-22W

### 21.5" Stainless Steel LCD Monitor



#### Specification

##### System:

- **OSD Input** : 5-key OSD buttons
- **OSD Function** : Contrast, Color, Position, Auto-adjustment, Factory Settings
- **Dimming** : 0~ 100% brightness dimming
- **Housing** : Anti-corrosion stainless steel
- **Mounting** : 100x100, 200x100 VESA Mount
- **IP Level** : Full-IP65 (5-side IP65 except I/O side)

##### Input / Output :

- **VGA** : 1 x VGA D-Sub 15 pin
- **DVI** : 1 x DVI-D
- **USB** : 1 x USB for touch
- **Power** : DC 9~36V

##### Power Specification :

- **Power Adapter** : No power adapter
- **Power Consumption** : 40W (typ.)

##### Panel Specification :

- **Size/ Type** : 21.5" TFT
- **Resolution** : 1920 x 1080
- **Brightness** : 250 cd/m<sup>2</sup>(typ.)
- **Contract Ratio** : 1000 : 1 (typ.)
- **Viewing Angle** : 170 (H) ; 160 (V)
- **Max. Colors** : 16.7M
- **Touch** : P-cap touch screen or 5-wire resistive touch

##### Environment Tolerance:

- **Operating Temperature** : -10 deg. C to 55 deg. C
- **Operating Humidity** : 10% to 95% (Non Condensing)
- **Storage Temperature** : -30 deg. C to 70 deg. C

##### Order Options :

- **High Brightness** : 1000 cd/m<sup>2</sup> (Optional)
- **Power Input** : 100~220V AC Input (Optional)
- **Custom I/O port** : By request

#### Drawings:

