

FIP-15R

15" Full-IP66/IP69K Stainless Steel LCD



Features:

- -20~60°C Wide Range Operating Temperature
- Anti-Corrosion Stainless Housing Design
- High Brightness: 1,000 nits for optional
- Slim & Curve Edge

Specification

System:

- Housing : Anti-corrosion stainless steel with deactivated coating
- Color : Sliver Color (Others by request)
- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto adjustment, Factory Settings
- Mounting : 100 x100 VESA Mount

IP66 I/O connectors :

- Video Input : 1 x VGA, (HDMI for optional)
- USB : USB for touch screen
- Power : AC 110~240V, Universal, ±10%

Power Specification :

- Power Adapter : No power adapter
- Power Consumption : 20W (typ.)

Panel Specification :

- Size/ Type : 15" TFT LCD
- Resolution : 1024 x 768
- Brightness : 250 (cd/m²)
- Contract Ratio : 500 : 1 (typ.)
- Viewing Angle : -70~70 (H) ; -60~60 (V)
- Max. Colors : 16.2M (6bits+ FRC)
- Touch : 5-wire resistive touch (default)

Environment Tolerance:

- Net Weight : 7.5 KG (Identity)
- Operating Temp. : -20 deg. C to 60 deg. C
- Storage Temp. : -40 deg. C to 80 deg. C
- Operating Humidity : 10% to 95% (Non Condensing) :
- IP level : Full IP66 / IP69K
- Vibration : MIL-STD-810G Method 514.6C-3
- Shock : MIL-STD-810G Method 516.6

Order Options :

- High Brightness : 1000 cd/m² (Optional)
- Touch Screen : P-cap touch screen(Optional)
- Power Input : 9~36V DC Input (Optional)
- Optical bonding : By request

Drawings:

