

Explosion Proof Non Contact Safety Interlock Switches



LM-Ex STAINLESS STEEL 316





II 2G Ex mb IIC T6 Gb



II 2D Ex mb IIIC T80 Db IP67*

Zones 1, 21, 2, 22 Gas and Dust



SALES NUMBER	TYPE ZONES 1,21,2,22	BODY HOUSING	CABLE LENGTH 6mm OD	CIRCUITS	ELECTRICAL RATING NORMALLY CLOSED CIRCUITS (Actuator Present)	ELECTRICAL RATING NORMALLY OPEN CIRCUITS (Actuator Present)
					RED/BLUE NC1 WHITE/BLACK NC2 INTERNALLY FUSED	ORANGE/BROWN NO
904101	LM-Ex	S/Steel	5M	2NC 1NO	230Vac/24Vdc 0.6A Max.	230Vac/24Vdc
904102	LM-Ex	S/Steel	10M	2NC 1NO	INTERNALLY FUSED	200mA. Max.

*Product is fully encapsulated which is considered to provide ingress protection to at least IP67.



SUMMARY SPECIFICATION AND SELECTION GUIDE:

SWITCH TYPE	HOUSING MATERIAL	PART NUMBER SERIES	MAXIMUM CURRENT	ZONES
WM1-Ex	Stainless Steel 316 and fitted with Stainless Steel Flexible Conduit	9001.....	0.6A	Zone 0 Gas Zone 20 Dust (An area where Gas and Dust are continuously present)
WM2-Ex	Stainless Steel 316	9002.....	2.0A	Zone 1 Gas Zone 21 Dust Zone 2 Gas Zone 22 Dust (An area where Gas and Dust is likely to occur in use)
CM1-Ex	Stainless Steel 316	901.....	2.0A	
CM2-Ex	Stainless Steel 316	902.....	1.0A / 0.6A	
CM3-Ex	Stainless Steel 316	903.....	0.6A	
LM-Ex	Stainless Steel 316	904.....	0.6A	
RM-Ex	Stainless Steel 316	905.....	0.6A	

TECHNICAL AND SAFETY SPECIFICATIONS:

Standards: IEC/EN60079-0 IEC/EN60079-18
ISO14119 EN60947-5-3 EN60204-1
ISO13849-1 EN62061

Safety Classification and Reliability Data:
Mechanical Reliability B10d
ISO13849-1
Safety Data – Annual Usage
Contact Release Time
Initial Contact Resistance
Minimum Switched Current
Insulation Resistance
Recommended Setting Gap

3.3 x 10⁶ operations at 100mA load
Up to PLe depending upon system architecture
8 cycles per hour/24 hours per day/365 days
MTTFd 470 years
<2ms
<500 milliohm
10Vdc 1mA
100 Mohms
5mm

Switching Distance
(Target to Time)
Approach Speed
Temperature Range
Enclosure Protection
Shock Resistance
Vibration Resistance
Body Material
Cable Type
Mounting Position
Approval Body

Sao 10mm Close
Sar 22mm Open
200mm/m to 1000mm/s
-20/+80 (or +60C for 2A version)
IP67
IEC 68-2-27 11ms 30g
IEC 68-2-6 10-55Hz 1mm
Stainless Steel 316
6mm OD
Any
BASEEFA UK

*Product is fully encapsulated which is considered to provide ingress protection to at least IP67.